



Bike Specifications

Harley Davidson FLHTK Electra Glide Ultra Limited

At Ride Australia Bike Tours

Make Model	Harley Davidson FLHTK Electra Glide Ultra Limited
Engine	Twin Cam 103™ with integrated oil cooler Valves Pushrod-operated, overhead valves with hydraulic, selfadjusting lifters; two valves per cylinder
Bore x Stroke	98.4 x 111.25 mm
Cooling System	Air
Compression Ratio	10.0:1
Exhaust	Chrome, 2-1-2 dual exhaust with tapered mufflers
Induction	Electronic Sequential Port Fuel Injection (ESPFI)
Ignition	Single-fire, non-wasted, map-controlled spark ignition
Starting	Electric
Max Torque	100 ft. lbs. 135 Nm @ 3250 rpm
Clutch	Multi-plate, wet



Transmission	6 Speed
Final Drive	Belt
Gear Ratio	1st 9.593 / 2nd 6.650 / 3rd 4.938 / 4th 4.000 / 5th 3.407 / 6th 2.875
Frame	Mild steel; tubular frame; two-piece stamped and welded backbone; cast and forged junctions; twin downtubes; bolt on rear frame with forged fender supports; MIG welded
Front Suspension	41.3 mm telescopic, cartridge-style damping
Rear Suspension	Swingarm Mild steel; two-piece drawn and welded section; forged junctions; MIG welded, Rear Shocks Air-adjustable
Front Brakes	2x 300mm disc 4 piston caliper ABS
Rear Brakes	Single 300mm disc 4 piston caliper ABS
Wheels Front	Contrast Chrome Impeller Cast Aluminum
Wheels Rear	Contrast Chrome Impeller Cast Aluminum
Front Tyre	BW 130/80B17 65H
Rear Tyre	BW 180/65B16 81H
Rake	26°
Trail	170 mm
Dimensions	Length 2600 mm / 102.4 in.
Wheelbase	1625 mm / 64 in.
Seat Height	Laden 695 mm / 27.3 in Unladen 740 mm / 29.1 in
Gross Vehicle Weight Rating	616.9 kg / 1360 lb
Wet Weight	414 kg / 896 lbs

Oil Capacity

3.8 Litres / 4 qt.

Fuel Capacity

22.7 Litres / 6 gal

